

## PFA RTD WIRE Duplex Unshielded

## **PRODUCT DESCRIPTION**

Conductor	Stranded			
AWG Sizes	#16 AWG - #26 AWG			
<b>Insulation</b> / <b>Jacket Type</b>	(PFA ) 260C			
Color Code	2C (Red / White) / Jacket (White)			
<b>Conductor Material</b>	ctor Material Nickel Plated Copper			
Shield Type	Unshielded / Duplex			
Approvals	Rohs / Reach Compliant			
Applications	Resistance Temperature Detectors / Thermometers / Sensors			
<b>Physical Properties</b>	Excellent resistance to abrasion, oil, moisture, acid and low smoke			

Part#	Conductor	Insulation Thickness	Overall Diameter *	Weight lbs/k ft	Temp Rating	Voltage
R1692D2P	16/19	.006"	.085" x .150"	21.8	260C	n/a
R1892D2P	18/19	.006"	.079" x .138"	17.5	260C	n/a
R2072D2P	20/7	.006"	.070" x .120"	12.3	260C	n/a
R2272D2P	22/7	.006"	.062" x .104"	8.5	260C	n/a
R2472D2P	24/7	.006"	.056" x .092"	6.3	260C	n/a
R2672D2P	26/7	.006"	.051" x .082"	4.6	260C	n/a